

WEATHERCOAT FLEX PRIMER

Product Description

Weathercoat Flex Primer is a water-based 100% acrylic sealer designed with:

- Excellent adhesion to concrete, brick walls and plastered surfaces
- Good alkali resistance
- Outstanding durability
- Low toxicity and odour
- Environment friendly

Designed Use

Area of Use: Interior and exterior

Substrate: As a sealer coat over concrete, brick walls and plastered surfaces prior to the application of Weathercoat Flex Primer

Technical Data

Product Reference: WB-1261

Finish: Glossy

Colour: Clear / White

Solids(%byvolume): 37±2

Specific Gravity: 1.32 ± 0.02

Thinner/Cleaner: Sweet Water

Theoretical Spread Rate

Approximately 7.0 m²/Litre depending on porosity of substrate.

Drying time	Substrate Temp.	Touch Dry	Touch Dry	Overcoating Interval	
				Minimum	Maximum
	25°C	20 minutes	40 minutes	2 hours	Indefinite

Application Data

Method of application : Conventional brush or roller

Surface Preparation

- The surface to be coated must be clean, dry and free from all loose extraneous materials (e.g., loose paints, dust, etc.) Remove all loose materials with a high pressure wash.
- If fungus is present, first treat with Berger Fungicidal Wash. Leave for 24 hours, then rinse and scrape away all fungus. For internal walls, wipe thoroughly with a damp cloth.
- If grease is present, clean using a mild detergent or solvent and rinse thoroughly with fresh water to ensure complete removal of the grease and the detergent.
- For new concrete substrate, ensure that it is completely cured prior to the application of a sealer. Moisture content should be below 6% when measured on the Sovereign Moisture Meter.

Storage and Handling

- **Storage:** Store in cool, dry condition.
- **Disposal:** Dispose as normal paint e.g., by controlled landfill. In case of doubt, consult local authority. Do not empty into drains, sewers or other water courses
- **Flash Point:** N/A
- **Shelf Life:** Upto 12 months

Safety Precaution

- Avoid contact with the skin and eyes. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream.
- Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray.
- Refer to MSDS for safe handling and application of this product.

First-Aid

- **Eyes:** In the event of accidental splashes, flush eyes immediately with warm water and obtain medical advice.
- **Skin:** Wash skin thoroughly with soap and water, or with an approved industrial cleaner. Do not use solvents.
- **Inhalation:** Move patient to fresh air, loosen collar and keep patient rested.
- **Ingestion:** Do not induce vomiting. Obtain immediate medical attention.

Disclaimer

The information provided in this data sheet is not intended to be complete. It is the responsibility of the user to ensure that the product used is suitable for the purpose it is meant to serve. In view of various factors affecting the performance of the coating, we cannot assume responsibility for the product performance, nor do we accept any liability arising from use of this product, unless specifically agreed to in writing by us. The information provided in the data sheet may be modified by us without notice.