

## WEATHERCOAT STONESHIELD PRIMARY COAT

### Product Description

A water thinnable coating with good alkali resisting properties designed to provide a sound base for Stoneshield Secondary Coat.

### Recommended Areas of Application

**Area of Use:** Interior and exterior

**Substrate:** Concrete, Plaster and Masonry.

### Technical Data

**Sheen Variants:** Matt, Smooth.

**Colours:** Black or limited shades.

**Volume Solids:** 26%

Theoretical Covering Capacity		
Recommended Dry Film Thickness per Coat		Theoretical Spread Rate
<b>Minimum</b>	25 microns	10.4 m <sup>2</sup> /Kg
<b>Maximum</b>	35 microns	7.43 m <sup>2</sup> /Kg
<b>Typical</b>	30 microns	8.70 m <sup>2</sup> /Kg

Practical Covering Capacity
For estimation of practical covering capacity, following factors to be taken into account: surface profile, uneven application, over spray, losses in container and equipment etc.

Drying time	Substrate Temp.	Touch Dry	Overcoating Interval	
			Minimum	Maximum
	20°C	2 hours	20 hours	Indefinite
	35°C	1 hour	16 hours	Indefinite
	45°C	½ hour	12 hours	Indefinite

### Application Data

**Method of Application** : Roller or brush

**Thinner** : Sweet water

**Thinning Ratio (by vol.)** : Use 5% to 10% sweet water for ease of application

### Surface Preparation

The performance of this coating is directly related to the degree of surface preparation.

- Ensure surface is clean, dry and free from all contaminants.
- Surface must be sound and free from laitance.
- Remove laitance by wire brush or sweep blast.

### Application Details

- Ensure adequate ventilation during application and drying.
- Do not apply when humidity exceeds 85% and condensation is likely.
- Surface temperature should be 3°C or more above dew point.
- Stir the contents thoroughly before and during use, with a broad flat stirrer, using an upward lifting action.

#### TYPICAL PAINT SYSTEM

##### Concrete

1 coat X Weathercoat Stoneshield Primary Coat

2 coats X Weathercoat Stoneshield Secondary Coat

1or 2 coats X Weathercoat Stoneshield Glaze Coat

For alternate system suggestion please contact Berger Paints Sales Representative

### Storage, Safety Information And Precautions

- Keep out of reach of children.
- Store in cool, dry conditions; ensure adequate ventilation during application.
- Avoid contact with skin and eyes; wear suitable protective clothing such as overalls, goggles, dust masks and gloves.
- Shelf life up to 12 month is from the date of manufacture.
- Flash Point: NA

### First-Aid

- Eyes: In the event of accidental splashes, flush eyes immediately with warm water and obtain medical advice.
- Skin: Wash skin thoroughly with soap and water, or with an approved industrial cleaner. Do not use solvents.
- Inhalation: Move patient to fresh air, loosen collar and keep patient rested.
- Ingestion: Do not induce vomiting. Obtain immediate medical attention.
- Dispose in landfill only.

### Disclaimer

*The information provided in this data sheet is not intended to be complete. It is the responsibility of the user to ensure that the product used is suitable for the purpose it is meant to serve. In view of various factors affecting the performance of the coating, we cannot assume responsibility for the product performance, nor do we accept any liability arising from use of this product, unless specifically agreed to in writing by us. The information provided in the datasheet may be modified by us without notice.*