

## WEATHERCOAT VINTAGE ALKALI RESISTANT PRIMER

### Product Description

A premium quality alkali resisting primer based on acrylic co-polymer designed to penetrate into, and seal the surface. It provides a sound base for improved adhesion of subsequent emulsion and conventional texture coating from the Berger range, and is ideal for both interior and exterior usage.

### Recommended Areas of Application

**Area of Use:** Interior and exterior

**Substrate:** Concrete, Plaster, Masonry, Brickwork and Block work.

### Technical Data

**Sheen Variants:** Matt, Smooth

**Colours:** White

**Volume Solids:** 37 ± 2%

Theoretical Covering Capacity		
Recommended Dry Film Thickness per coat		Theoretical Spread rate
<b>Minimum</b>	30 microns	12.33 m <sup>2</sup> /Ltr
<b>Maximum</b>	40 microns	9.25 m <sup>2</sup> / Ltr
<b>Typical</b>	35 microns	10.57 m <sup>2</sup> / Ltr

Practical Covering Capacity
For estimation of practical covering capacity, following factors to be taken into account: surface profile, uneven application, over spray, losses in container and equipment etc.

Drying time	Substrate Temp.	Touch Dry	Overcoating Interval	
			Minimum	Maximum
	25°C	90 minutes	6 hours	Indefinite
	35°C	60 minutes	5 hours	Indefinite
	45°C	30 minutes	4 hours	Indefinite

### Application Data

**Method of Application** : Roller, brush, Spray

**Thinner** : Sweet water

**Thinning Ratio (by vol.)** : Use 5% to 10% sweet water for ease of application depending on method of application.

### Surface Preparation

The performance of this coating is directly related to the degree of surface preparation.

- Ensure surface is clean, dry and free from all contaminants.
- Surface must be sound and free from laitance.
- Remove laitance by wire brush or sweep blast.

Note: Fungal growth should be treated with Bison Fungicidal Solution. After drying, one coat of Plastaseal Penetrating sealer should be applied.

### Application Details

- Ensure adequate ventilation during application and drying.
- Do not apply when humidity exceeds 85% and condensation is likely.
- Surface temperature should be 3°C or more above dew point.
- Stir the contents thoroughly before and during use, with a broad flat stirrer, using upward lifting action.
- Roller or Brush: Apply an even coat taking care to avoid runs and sags.

#### TYPICAL PAINT SYSTEM

1 coat x Weathercoat Vintage Alkali Resistant Primer

2 coats of Weathercoat Vintage Topcoat [As per desired effect]

2 coats x Weathercoat Vintage Glaze Coat. (Optional)

For alternate system suggestion please contact Berger Paints Sales Representative

### Storage, Safety Information And Precautions

- Keep out of reach of children.
- Store in cool, dry conditions; ensure adequate ventilation during application.
- Avoid contact with skin and eyes; wear suitable protective clothing such as overalls, goggles, dust masks and gloves.
- Shelf life up to 12 months from the date of manufacture.
- Flash Point: NA

### First-Aid

- Eyes: In the event of accidental splashes, flush eyes immediately with warm water and obtain medical advice.
- Skin: Wash skin thoroughly with soap and water, or with an approved industrial cleaner. Do not use solvents.
- Inhalation: Move patient to fresh air, loosen collar and keep patient rested.
- Ingestion: Do not induce vomiting. Obtain immediate medical attention.
- Dispose in landfill only.

### Disclaimer

*The information provided in this data sheet is not intended to be complete. It is the responsibility of the user to ensure that the product used is suitable for the purpose it is meant to serve. In view of various factors affecting the performance of the coating, we cannot assume responsibility for the product performance, nor do we accept any liability arising from use of this product, unless specifically agreed to in writing by us. The information provided in the datasheet may be modified by us without notice.*